



Satisfy Professional's Needs

Cordless Hammer Driver Drill

Cordless Driver Drill

DHP486 13 mm (1/2") / **DDF486** 13 mm (1/2")



**Compact
But high power**

18V
LITHIUM-ION

Max Lock Torque
125 N·m



Increased performance in continuous heavy-duty applications

Compact design

On top of the higher performance in continuous heavy-duty applications compared with the current model, shorter overall length is achieved by optimizing the design of the gear assembly.



All metal gear construction for extra-high transmission durability



Mechanical 2-speed transmission



Max clutch torque: 12 N·m

Due to the increased contact area of the clutch cam, the max clutch torque is increased, enabling to tighten a heavy-duty fastener such as a dia. 9.0x50mm lag bolt in screwdriving mode.

Twin LED job light with preglow and afterglow functions



Hi-speed Max. 2,100 RPM

High power

BL MOTOR



Variable speed control trigger

Cordless Hammer Driver Drill DHP486



Cordless Driver Drill DDF486



Belt clip

XPT
EXTREME PROTECTION TECHNOLOGY

Cordless Hammer Driver Drill		DHP486	13 mm (1/2")
Cordless Driver Drill		DDF486	13 mm (1/2")
Variable Speed	Capacity	DHP486	DDF486
Brake		Steel: 13 mm (1/2")	Steel: 13 mm (1/2")
Reversing		Wood (Auger-Bit): 50 mm (2")	Wood (Auger-Bit): 50 mm (2")
Mechanical 2-Speed		Wood (Self-Feed Bit): 76 mm (3")	Wood (Self-Feed Bit): 76 mm (3")
Keyless Chuck		Wood (Hole Saw): 152 mm (6")	Wood (Hole Saw): 152 mm (6")
Torque Setting 21		Masonry: 16 mm (5/8")	-
Built-in Job Light		Siding Board: 170 mm (6-11/16")	Siding Board: 170 mm (6-11/16")
Carrying Case		1.5 - 13 mm (1/16 - 1/2")	1.5 - 13 mm (1/16 - 1/2")
	Chuck Capacity	-	-
	Impacts Per Minute (IPM)	High / Low: 0 - 31,500 / 0 - 8,250	High / Low: 0 - 2,100 / 0 - 550
	No Load Speed (RPM)	High / Low: 0 - 2,100 / 0 - 550	High / Low: 0 - 2,100 / 0 - 550
	Max Fastening Torque	Hard / Soft: 130 / 65 N·m (1,150 / 580 in.lbs.)	Hard / Soft: 130 / 65 N·m (1,150 / 580 in.lbs.)
	Max Lock Torque	125 N·m (1,100 in.lbs.)	125 N·m (1,100 in.lbs.)
	Dimensions (L x W x H)	w/o Battery: 178 x 81 x 217 mm (7 x 3-3/16 x 8-1/2")	w/o Battery: 178 x 81 x 217 mm (7 x 3-3/16 x 8-1/2")
		w/ BL1830B / BL1840B / BL1850B / BL1860B:	w/ BL1830B / BL1840B / BL1850B / BL1860B:
		178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")	178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")
	Net weight	2.3 - 2.7 kg (5.1 - 6.0 lbs.)	2.3 - 2.6 kg (5.1 - 5.7 lbs.)

Standard Equipment: Depth Gauge(DHP486 only), Side Handle, Belt Clip, (+)(-) Bit, Bit Holder, Charger, Battery

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202012